

Lothar W. Nordheim

1594

A-670

Date 1/14/44


Subject (STACK ACTIVITIES)

By Nordheim

LUC No.

File _____

Those Eligible
To Read The
Attached



Copy # 1 Newson

To Newson

This document has been approved for release
to the public by:

David R. Hennin 4/2/95
Technical Information Officer
ORNL Site Due

Before reading this document, sign and date below

Name _____ Date _____
NITED

JAN 22 1944

A. W. NEWSON

Name _____ Date _____

Dr. L.W. Nordheim
The University of Chicago
Metallurgical Laboratory

BUTTERFIELD 4300

January 14 , 1944

Dr. H.W. Newsome
c/o Dr. H.D. Whittaker
Clinton Laboratories
P.O. Box 1991
Knoxville, Tenn.

Dear Newsome.

CLASSIFICATION CANCELLED

DATE SEP 20 1963
For The Atomic Energy Commission

H.B. Canall
Chief, Declassification Branch

I am sorry that I was unable to give you the complete answer to the question of the stack activities on Wednesday evening, but I was very tired and rushed. Here is my very simple analysis of the problem which, I feel sure, is the same as your own.

The following notation is used :

P = activity produced in ~~pile~~ air per (sec cm³) in pile
 $a_{1,2}$ = specific activities in duct air and pile air
 $A_{1,2}$ = total activities produced by duct air and trapped air
 $V_{1,2}$ = volumes of ducts and of air pockets respectively
 κ_1 = argon period = (1/110 min)
 κ_2 = relaxation period of trapped air = (1/73 min)
 $(\kappa_1 + \kappa_2) = (1/44 \text{ min })$ observed)

The contribution of the duct air to stack activity is then simply

$$I A_1 = V_1 P$$


(the transit time in the pile is so short that decay during transit is negligible)

The specific activity of the trapped air is determined by

$$\frac{da_2}{dt} = - \kappa_1 a_2 - \kappa_2 a_2 + P$$

or in the steady state

This document contains neither recommendations nor conclusions of the National Defense Science Commission or of the Atomic Energy Commission. It is the property of the Commission and is loaned to authorized personnel; its transmission to an unauthorized person is prohibited by law.



The University of Chicago

Metallurgical Laboratory

BUTTERFIELD 4300

Dr. E.W. Newsome 2

$$a_2 = \frac{P}{K_0 + K_2}$$

To obtain the contribution to the stack activity, multiply by rate of escape

$$\frac{dV_2}{dt} = - K_2 V_2$$

that is

$$II \quad A_2 = K_2 V_2 \frac{P}{K_2 + K_0}$$

Let the ratio of activities after and before shut down be

$$r = \frac{A_2}{A_1 + A_2}; \quad A_2 = A_1 \frac{r}{1-r}$$

then from I and II

$$III \quad V_2 = V_1 \frac{r}{1-r} \frac{K_0 + K_2}{K_2}$$

With $r = 1/2$ and the observed values for K_0, K_2

$$V_2 = 1.66 V_1$$

This means that $\sim 1/12$ of the graphite volume is filled by air which can escape readily. This seems to be quite reasonable.

I suppose, we will arrive in Oak Ridge on January 24 or 25. Looking forward to seeing you then

Yours very sincerely

L.W. Nordheim

L.W. Nordheim